STRONG AND LIGHT!

Claro™ Grow is a lightweight fabric membrane that lets the light through and has excellent strength for longer life. All layers of Claro Grow are translucent, allowing light to penetrate every layer of the fabric, giving it one of the highest translucency percentage on the market. Claro Grow is woven from high-density polyethylene slit tapes and coated on both sides with low-density polyethylene.



FEATURES & BENEFITS

- Cradle to Cradle Certified® Bronze
- Enhanced UV protection for longer service life
- High strength-to-weight ratio
- Lightweight material making installation easier and faster while reducing cost
- Excellent light transmittance in the PAR region for photosynthesis (400nm to 700nm)
- Dirt repelling LDPE coating
- Excellent tear resistance
- 3 to 5 year warranty



Standard Woven Scrim

CERTIFIED

cradle to cradle



Engineered Coating

Woven Reinforcement

Engineered Coating







PRODUCT ATTRIBUTES

CHARACTERISTICS	Claro™ Grow Light RU210, 1.75 Structure Fabric	Claro™ Grow RU6-6, 1.75 Structure Fabric	Claro™ Grow RU8-6, 1.75 Structure Fabric
Weave	Woven Clear HDPE Tapes	Woven Clear HDPE Tapes	Woven Clear HDPE Tapes
Coating	LDPE with UV stabilizers 1.75 mil (42 g/m²)/side	LDPE with UV stabilizers 1.75 mil (42 g/m²)/side	LDPE with UV stabilizers 1.75 mil (42 g/m²)/side
Light Transmittance (ASTM D3786)	Visible (PAR) 83%	Visible (PAR) 83%	Visible (PAR) 82%
Weight	5.5 oz/yd² (186 g/m²)	5.5 oz/yd² (186 g/m²)	6.0 oz/yd² (203 g/m²)
Cores	4" or 5" I.D. available	4" or 5" I.D. available	4" or 5" I.D. available
Width	Up to 144"(-0, +0.5)	Up to 144"(-0, +0.5)	Up to 144"(-0, +0.5)
Length	Minimum 500 yds/roll; up to 2000 yds/roll (1829 m)	Minimum 500 yds/roll; up to 2000 yds/roll (1829 m)	Minimum 500 yds/roll; up to 2000 yds/roll (1829 m)
Colors	Clear	Clear	Clear
Limited Warranty	3 years	3 years	5 years

These values are typical data and are not intended as limiting specifications.

PRODUCT APPLICATIONS

Greenhouses

MARKETS

- Agriculture
- Greenhouse





